

How to activate the license for a network version protected with HASP HL Net protection key ?



HASP HL Net key

- 1) Download from www.zace.com/versions/Hasp/HASPUserSetup.exe and install drivers for HASP HL protection key.

Please note that HASP network dongle uses TCP/UDP port 1947 for local (LAN only) communication. This port must not be blocked in order for a station to access the network license.

- 2) Run the ZSoil Protection Manager
(Start\All Programs\ZSoil 2013\Tools\ ZSoil Protection Manager)

ZSoil Protection Manager 2013

HDD ID: 8E05-5ADB

Protection type

Software (z_soil2013.pro is required) - user defined location Prepare software key for activation

Path to z_soil2013.pro: C:\zprt\z_soil2013.pro Browse

Hardware (USB key with z_soil2013.pro is required)

Hardware (HASP key is required) Update HASP key

Network

IP address or server name (not required for HASP key):

Return a license Show borrowed licenses

Computer name	HDD ID	Valid to
---------------	--------	----------

Help
Cancel
OK

- 3) Choose the **Hardware (HASP key is required)** protection type and check **Network** flag
- 4) Please close ZSoil Protection Manager with OK button

- 5) Status of the HASP key is monitored by Sentinel Admin Control Center.
Run **http://localhost:1947** in a web browser in order to display current status of the HASP key.

